

# FEC AerPPC Series



Side USB I/O for Add-on Devices



AerPPC PP-1635



Intergrated Customer Display



AerArm with 2nd Display

## SPECIFICATIONS

Model	PP-1635
LCD Display	15" TFT LCD Panel
Resolution	1024 x 768
Touch Panel	P-CAP (10-points touch)
CPU	BayTrail Celeron J1900 2.0 - 2.4 GHz
RAM	4GB DDR3 (up to 8GB)
Storage	64GB SSD
Construction	Aluminum Die-casting + Plastic
Serial Port	4 x COM (RJ45 x 2, DB9 x 2)
USB Port	5 x USB (USB2.0 x 4, USB3.0 x 1)
Cash Drawer Port	1 x RJ11 (12V)
LAN Port	1 x RJ45 Gigabit LAN
Video Port	1 x VGA (12V optional Selectable in BIOS)
DC Input	1 x 12V DC
DC Output	1 x 12V DC
Power Supply	60W Adapter
Operation System	Windows 7, POSReady 7, Windows 10
Dimension (W x H x D)	366 mm x 335 mm x 220 mm

\*Specifications are subject to change without notice.

# AERPPC

**Fanless All in one Panel PC:** Featuring Intel Celeron J1900 quad-core CPU, the fanless 15" PP1635C is a perfect POS solution. With its small footprint, it also creates more space for work efficiency.

**True flat P-CAP touch:** Featuring elegant and graceful bezel-free design. The sensitivity of P-CAP touch fulfills customers' demands based on different user scenarios.

**Aluminum Die-casting housing:** It is not only robust and durable but also provides a great solution for heat dissipation for CPU, RAM, and storage.




## ULTRA SLIM

The total thickness of PP-1635C is from 27.9 to 41.7mm. It is not only slim but also with strong and durable aluminum design to maximize your working space.



## EASY SWAP STORAGE

Loose one single screw then you will be able to access the storage for easy maintenance.



## CABLE MANAGEMENT

To avoid messy cabling in working area, we offer a solution that cables can be hidden within the back cover of the stand to make working area always clean and tidy.

