

AerPOS

15inch or 17inch High Performance POS System



FEC

AerPOS

We aim to exceed your expectations by providing high quality, reliable products with state of the art designs.

AerPOS is an elegant and powerful all-in-one system, designed to be used in the toughest retail and hospitality environments. It is a very durable and compact system that fits beautifully on any point of sale counter. The modular design features also ensures high serviceability.

Add-on Devices

All AerPOS add-on devices use a USB interface for reliability, simple installation and maintenance.

USB I/O is on the right side of the display



Peripherals



The integrated customer display can be turned and tilted for the best viewing angle.



11.6inch second display with bracket



15inch second display (pole type)

Features



OSD Controls: Display brightness, display power on/off (on 15inch models)



Smart Fan detects CPU temperature and adjusts fan speed automatically



Standard Colors: Black + Silver; Black + Red; White + Silver



One-step operation for quick access to hard disk or SSD




The display can be easily removed for easy maintenance



CPU module can be extracted for efficient upgrades and maintenance

Customer Display



- LCD w/ LCD Backlight
- 25-30nits

11.6 inch 2nd Display



- Max resolution: 1366 x 768
- 200 nits

15inch 2nd Display



- Max resolution: 1024 x 768
- Option of 250 / 450nits

Specifications

Model	AP-3615	AP-3617	AP-3625
Processor	Intel® Celeron® G540, 2.5Ghz Intel® Core i3-2120, 3.3Ghz Intel® Core i5-3550S, 3.0Ghz		Intel® Celeron® B810, 1.6Ghz Intel® Core i5-2510E, 2.5Ghz (vPro)
System Memory	2GB Standard, Maximum 8GB (1x204-pin DDR3)		
Power Supply	150W (12V / 12.5A) External Power Adaptor		
Storage Device	1 x 2.5" SATA HDD or SSD		
Chipset	Intel® H61		Intel® QM67
Speaker	Internal Speaker 2W x 2		
Construction	Aluminum Die-casting + Plastic + Glass		
Housing Color	Black with Silver Trim; Black with Red Trim; White with Silver Trim		
Touch LCD Display			
Size / Resolution	15" TFT-LCD / 1024 X 768	17" TFT-LCD / 1280 X 1024	15" TFT-LCD / 1024 X 768
Brightness (Backlight Type) & Touch Screen	350 cd/m ² (LED); 5-Wire Resistive Touch / Projected Capacitive Touch	250 cd/m ² (LED); 5-Wire Resistive Touch / Projected Capacitive Touch 350 cd/m ² (LED); 5-Wire Resistive Touch / Projected Capacitive Touch	350 cd/m ² (LED); 5-Wire Resistive Touch / Projected Capacitive Touch
I/O Ports			
Serial Port	4 x External: COM 1, COM 2 (DB9), COM 3, COM 4 (RJ45)		
USB Port	5 x External (4 Rear + 1 Side)		
Cash Drawer Port	1 x RJ11 (12V)		
LAN Port	1 x RJ45 Gigabit LAN		
Audio Port	1 x Line Out, 1 x Mic In		
Video Port	1 x VGA		
DC Output	1 x 12V DC Jack 2.5 mm		
Optional I/O Board			
Type A	Serial Port: COMA (DB9); 1 x Powered USB 12V; 2 x USB		
Type B	1 x Powered USB 24V		
Type C	2 x Powered USB 12V; 1 x Powered USB 24V		
OS Supported			
Windows	Windows XP, POSReady 2009, Windows 7, POSReady 7, Windows 10 Enterprise		
Dimensions & Weight			
Product (W x H x D)	370 x 360 x 235 mm, 7.1 Kg	410 x 386 x 235 mm, 10 Kg	370 x 360 x 235 mm, 7.1 Kg
Carton (W x H x D)	480 x 460 x 320 mm, 9.1 Kg	560 x 540 x 360 mm, 11 Kg	480 x 460 x 320 mm, 9.1 Kg

*Specifications are subject to change without notice.