

# BP-864

High Performance Compact Box System



**FEC**

# BP-864

**BP-864, the world's first box system that is a compact pc and an All-in-One POS when integrated with a monitor, fulfills it all for various types of business solutions.**

BP-864 equips with latest Intel® H81 Chipset and offers selections of Intel® Celeron®, Core i3 or Core i5 processors for flexible applications. With FEC revolutionary design, BP-864 delivers the best modularity. Optional 2nd I/O interfaces provide more availabilities to fit various situations. BP-864 is the ideal choice for all retailers and hospitality business.



## Features



Standard Type



Type C: COM Port (RJ45) + Power USB



Type G: Power USB



Type K: COM Port (DB9) + Power USB



CPU box and case can be easily detached to upgrade and maintain.



One step access to the SATA HDD or SSD for easy serviceability.



Supported M.2 socket interface.

- Combine BP-864 with AerMonitor and other add-on devices for a complete point of sale solution.
- Multiple I/O interface choices for different applications
- Can be used as a kiosk engine to power self-service solutions
- Modular design for easy serviceability



Power button, hard disk indicator and USB port is located in the front face for quick maintenance.




The thermal fin design on BP-864 increases heat transfer effectiveness, keeping it cool



BP-864 can be easily mounted onto any flat surface.



It is extremely compact measuring at 29 centimeters in width, 4.3 centimeters in height and 22.6 centimeters in depth.



BP-864 weighs only 2.8 kilograms



BP-864 CPU box can be integrated to various sizes of FEC Aer Panel PC.

<b>Model</b>		<b>BP-864</b>
Processor	Intel® Celeron G1820TE 2.20GHz Intel® Core i3-4330TE 2.40 GHz Intel® Core i5-4590T 3.0 GHz	
System Memory	1 x 2GB Standard, Maximum 16GB (2 x 8GB 204-pin DDR3L-1600)	
Power Supply	150W (12V / 12.5A) External Power Adaptor	
Storage Device	1 x 2.5" SATA HDD or SSD	
Second Storage	Optional M.2 Storage Device	
Construction	Aluminum Die-casting + Plastic	
Housing Color	Black with Silver Trim	
<b>I/O Ports</b>		
Serial Port	1 x External: COM1 (RJ45) with RI / 5V / 12V Selectable	
USB Port	5 x External (Rear USB 2.0 x 2, USB 3.0 x 2; Front USB 2.0 x 1)	
Powered USB Port	1 x 24V	
Cash Drawer Port	1 x RJ11 (12V / 24V)	
LAN Port	1 x RJ45 Gigabit LAN	
Video Port	2 x	
DC Input	1 x 12V DC	
DC Output	1 x 12V DC Jack 2.5 mm	
<b>Optional I/O Board (Factory Install Only)</b>		
Type C	2 x Serial Port: COM 2 & COM 3 (RJ45) RI / 5V / 12V Selectable; 1 x 12V Powered USB Port	
Type G	3 x 12V Powered USB Port	
Type K	1 x Serial Port: COM 2 (DB9) RI / 5V / 12V Selectable; 2 x 12V Powered USB Port	
<b>OS Supported</b>		
Windows	Windows 7, Windows Embedded POSReady 7, Windows 8.1, Windows Embedded 8.1 Industry, Windows 10 Enterprise	
<b>Dimensions &amp; Weight</b>		
Product (W x H x D)	290 x 43 x 226 mm, 2.8 Kg	
With Carton (W x H x D)	510 x 144 x 328 mm, 4.7 Kg	
<b>Operation Conditions</b>		
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)	
Storage Temperature	20°C ~ 60°C (-4°F ~ 130°F)	

\*Specifications are subject to change without notice.